

Product Specifications

Style Number	WPL1003	
Construction	Laminate	
Edge Profile	v-groove with painting	
Nominal Dimensions	7.8"wide, 48"long	
	US Units	Metric Units
Actual Product Width	7.8"	19.8cm
Actual Product Length	48"	121.8cm
AC rating	AC4	
Overall Product Thickness	0.39"	10mm
Core Thickness	0.31"	8mm
Attached Underlayment	blue embossed pad	
Attached Underlayment Thickness	0.08"	2mm
Surface Texture	Random EIR	
Wearlayer Coating	Aluminum Oxide	
Installation Methods	floating	
Profile	Angle/tap	
Country of Origin	Made in China	
Waterproof	Yes, featuring LOTO Tech Plus waterproof technology	

Packaging

Area per Box	15.58 sqft	1.45 sqm
Pieces per Box	6 pcs	
Weight per Box	22.47lbs	10.19 kg
Boxes per Pallet	50 boxes	



WPL1003

Colors of 10mm Waterproof Laminate

WPL1001-2001-3



WPL1003-2008-2



WPL1002-2007-006



WPL1004-3106-6



Colors of 10mm Waterproof Laminate



The list of colors above complements the entire range of colors available for the current product.

Performance & certifications

Environmental Attributes:

- DDC laminate is certified to a standard that is set by the North American Laminate Flooring Association (NALFA), called the NALFA LF-01 standard. This standard requires 3rd party testing, and includes the "CARB" standard.
- High Recycled Content
- FloorScore certified, complying to strict indoor air-quality standards
- Low VOC adhesives & finishes
- Replication of natural looks using advanced printing technology
- Scratch Resistant: ScratchResist
- Steam Mop Approved: Yes
- Fade and Stain Resistant: Yes
- Can be installed on a wall: Yes

Warranties

25 Year Limited (Lifetime) Structural Warranty for WPL/WPL HD Premier

20 Year Limited Residential Wear Warranty

5 Year Limited Commercial Wear Warranty

The warranty will not cover installations practices not consistent with manufacturer's install & care guidelines.

PERFORMANCE	TEST STANDARD	REQUIREMENT	CONCLUSION
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	76
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	73



www.greentouchflooring.com

DDC TEXAS INC. 1461S Belt Line Rd #300, Coppell, TX 75019 (469) 906-2787 office@ddcfloors.com

DDCC North America INC. 5026 Harding Pl, Nashville, TN 37211 (865)249-4754 office@ddcfloors.com

DDCC GLOBAL SOURCING INC. 330 King St, Elk Grove Village, IL 60007, USA (773)704-0439 office@ddcfloors.com

Product Specifications

Style Number	WPL1203	
Construction	Laminate	
Edge Profile	v-groove with painting	
Nominal Dimensions	9.41"wide, 59.06"long	
	US Units	Metric Units
Actual Product Width	9.41"	23.9cm
Actual Product Length	59.06"	150.0cm
AC rating	AC4	
Overall Product Thickness	0.47"	12mm
Core Thickness	0.47"	12mm
Surface Texture	EIR/wood texture	
Wearlayer Coating	Aluminum Oxide	
Installation Methods	floating	
Profile	Angle/tap	
Country of Origin	Made in China	
Waterproof	Yes, featuring LOTO Tech Plus waterproof technology	

Packaging

Area per Box	15.44 sqft	1.43 sqm
Pieces per Box	4 pcs	
Weight per Box	33.38 lbs	15.14 kg
Boxes per Pallet	44 boxes	



WPL1203

Colors of 12mm Waterproof Laminate

WPL1201-A902-3101-6



WPL1204-A906-3105-6



WPL1202-A905-3105-1



WPL1205-A908-3108-7



WPL1203-3105L-3



WPL1206-3201-5



Colors of 12mm Waterproof Laminate



The list of colors above complements the entire range of colors available for the current product.

Performance & certifications

Environmental Attributes:

- DDC laminate is certified to a standard that is set by the North American Laminate Flooring Association (NALFA), called the NALFA LF-01 standard. This standard requires 3rd party testing, and includes the "CARB" standard.
- High Recycled Content
- FloorScore certified, complying to strict indoor air-quality standards
- Low VOC adhesives & finishes
- Replication of natural looks using advanced printing technology
- Scratch Resistant: ScratchResist
- Steam Mop Approved: Yes
- Fade and Stain Resistant: Yes
- Can be installed on a wall: Yes

Warranties

25 Year Limited (Lifetime) Structural Warranty for WPL/WPL HD Premier

20 Year Limited Residential Wear Warranty

5 Year Limited Commercial Wear Warranty

The warranty will not cover installations practices not consistent with manufacturer's install & care guidelines.

PERFORMANCE	TEST STANDARD	REQUIREMENT	CONCLUSION
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	76
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	73



www.greentouchflooring.com

DDC TEXAS INC. 1461S Belt Line Rd #300, Coppell, TX 75019 (469) 906-2787 office@ddcfloors.com

DDCC North America INC. 5026 Harding Pl, Nashville, TN 37211 (865)249-4754 office@ddcfloors.com

DDCC GLOBAL SOURCING INC. 330 King St, Elk Grove Village, IL 60007, USA (773)704-0439 office@ddcfloors.com