

# SUMMIT SILVER

## 48.3"x7.36"x2mm Dry Back Flooring

### Product Specifications

|                     |              |
|---------------------|--------------|
| <b>SKU</b>          | SS2005       |
| <b>Construction</b> | LVT          |
| <b>Width</b>        | 7.36"        |
| <b>Length</b>       | 48.3"        |
| <b>Wearlayer</b>    | 6mil         |
| <b>Thickness</b>    | 2mm          |
| <b>Surface</b>      | Wood texture |
| <b>Edge</b>         | Square       |
| <b>Gloss Level</b>  | Normal       |
| <b>Waterproof</b>   | Yes          |



### Packaging

|                         |                  |
|-------------------------|------------------|
| <b>Area per Box</b>     | 49.4sqft/4.59sqm |
| <b>Weight per Box</b>   | 38.37lbs/17.44kg |
| <b>Pieces per Box</b>   | 20pcs            |
| <b>Boxes per Pallet</b> | 60box            |

### Color

SS2001



SS2002



SS2003



SS2004



SS2005



[www.greentouchflooring.com](http://www.greentouchflooring.com)

### Product Specifications

|                     |              |
|---------------------|--------------|
| <b>SKU</b>          | SG2005       |
| <b>Construction</b> | LVT          |
| <b>Width</b>        | 7.36"        |
| <b>Length</b>       | 48.3"        |
| <b>Wearlayer</b>    | 12mil        |
| <b>Thickness</b>    | 2mm          |
| <b>Surface</b>      | Wood texture |
| <b>Edge</b>         | Square       |
| <b>Gloss Level</b>  | Normal       |
| <b>Waterproof</b>   | Yes          |

### Packaging

|                         |                  |
|-------------------------|------------------|
| <b>Area per Box</b>     | 49.4sqft/4.59sqm |
| <b>Weight per Box</b>   | 38.37lbs/17.44kg |
| <b>Pieces per Box</b>   | 20pcs            |
| <b>Boxes per Pallet</b> | 60box            |



SG2005

### Color

SG2001



SG2002



SG2003



SG2004



SG2005



[www.greentouchflooring.com](http://www.greentouchflooring.com)

# SUMMIT PLATINUM

## 48.3"x7.36"x2.5mm Dry Back Flooring

### Product Specifications

|                     |              |
|---------------------|--------------|
| <b>SKU</b>          | SP2005       |
| <b>Construction</b> | LVT          |
| <b>Width</b>        | 7.36"        |
| <b>Length</b>       | 48.3"        |
| <b>Wearlayer</b>    | 20mil        |
| <b>Thickness</b>    | 2.5mm        |
| <b>Surface</b>      | Wood texture |
| <b>Edge</b>         | Square       |
| <b>Gloss Level</b>  | Normal       |
| <b>Waterproof</b>   | Yes          |

### Packaging

|                         |                   |
|-------------------------|-------------------|
| <b>Area per Box</b>     | 39.52sqft/3.67sqm |
| <b>Weight per Box</b>   | 38.37lbs/17.44kg  |
| <b>Pieces per Box</b>   | 16pcs             |
| <b>Boxes per Pallet</b> | 60box             |



SP2005

### Color

SP2001



SP2002



SP2003



SP2004



SP2005



[www.greentouchflooring.com](http://www.greentouchflooring.com)

## Warranties

Commercial Warranty 15 Years

The warranty will not cover installations practices not consistent with manufacturer's install & care guidelines.

## CERTIFICATIONS

|            |           |
|------------|-----------|
| FloorScore | Certified |
| ISO        | Certified |
| CE         | Certified |

| DESCRIPTION                 | TEST METHOD  | RESULT  |
|-----------------------------|--|---|
| Overall Thickness           | EN ISO 10582(ISO 24346)                                | Pass  |
| Thickness of Wear layer     | EN ISO 10582(ISO 24340)                                | Pass  |
| Length / Width / Squareness | EN ISO 10582(ISO 24342)                                | Pass  |
| Residual indentation        | EN ISO 10582(ISO 24343-1))                             | Pass  |
| Dimensional Stability       | EN ISO 10582(ISO 23999-18)                             | Pass  |
| Total mass per unit area    | EN ISO 10582(ISO 23997)                                | Pass  |
| Effect of castor chair      | EN ISO 10582(ISO 4918)                                 | Pass  |
| Wear resistance             | EN 660-2   | Wear Group :P   |
| Flexibility                 | EN ISO 10582(ISO 24344:2008 Method A)                  | Pass  |
| Color fastness to light     | EN ISO 10582(ISO 105-B02:2014, Method 3)<br>ASTM F1515 | ≥Grade 6<br>△E≤8  |
| Slip Resistance             | DIN 51130(EN 13893)                                    | R10   |
| Chemical Resistance         | EN 438-2:2005 section 26                               | Grade 5   |
| Classification              | ISO 10582  | Class 21:Domestic/Moderate/Light  |
| Reaction to Fire            | EN 13501-1(ISO 9239-1)(ISO11925-2)<br>ASTM E648-06     | Bf -s1<br>Critical Radiant Flux :>1.08(W/cm2)                             |
| Smoke Density               | ASTM E662  | Nonflaming condition Max. Ds : 293.7<br>Flaming condition Max. Ds : 258.7 |
| Fungi Resistance test       | ISO 846:1997   | Intensity of growth 0   |
| Heavy Metal                 | EN-71-3  | N.D   |
| Phtalates(6 type)           | EN 14372   | N.D   |

[www.greentouchflooring.com](http://www.greentouchflooring.com)